★ 密· 答ir



NO.2119010459



VAS LINE 货物运输条件鉴定书

Certification for Safe Transport of Chemical Goods

锂电池 -符合包装说明970第∐部分

Alpha TD80S温度记录仪(内置柱型锂电池LS14500 3.6V 2600mAh) 样品名称:

Alpha TD80S Temperature Data Logger Sample name:

上海腾森电子科技有限公司 委托单位: TempSen Electronics Company

上海腾森电子科技有限公司 生产单位: TempSen Electronics Company



测有阻公司

Shanghai Research Institute of Chemical Industry Testing Co., Ltd

货物运输条件鉴定书

Certification for Safe Transport of Chemical Goods

		- j	Certification for Safe Trans	sport of Chemic	cal Goods	1 age 17 e	
样品名		中文 Chinese	se				
Samp		英文 English	Alpha TD80S Temperature Data Logger				
委托单位 Consignor		1.7	上海腾森电子科技有限公司 TempSen Electronics Company				
生产单位 Manufacturer			上海腾森电子科技有限公司 TempSen Electronics Company 国际航空运输协会《危险品规则》60版				
检验方法、程序 Inspection method and procedure 样品外观			A Table House				
	包装	appearance 件信息 information	锂电池总净重≤5kg。 Lithium batteries tota	ANDER	≤5kg.	放置方式	
序号 NO.	号电池种类		型号 Model		容量Capacity /锂含量Li content	放置方式 Placement 安装在设备内	
1	不可?	充电锂金属电池芯ry Li-metal cell	LS14500		2600mAh / 0.7g	Contained in equipment	
鉴	I DEN	锂金属电池。 Lithium metal 1 2. 空运按照国 DCR)	际航空运输协会《危险	品规则》办理	WA BIT STORY	according to IATA of Packaging Instruction	
定	8	970. 3 句装要求(Packaging requirements)					
结	CONCLUS	按包装说明970第II部分要求办理。 The goods are packaged according to the Packaging Instruction 970 section II.					
论	NO ISN	检验日期 Inspection D	: Date: 2018-12-11	签发日期: Issue Date:	2018-12-11	生效日期: 2019-01-01 Effective Date: 2019-01-01	
	·注 nment	这种设备不会产 信号(如蜂鸣警打 These devices meet defined s interfere with	生危险的放热,在开启状态下限,闪光灯)。 are not capable of generat	ing a dangerous	evolution of heat. Who	空器系统产生干扰、不会发出干打 en active, these devices must tion of the device does not disturbing signals (such as	

批准 Approver: 指小W

审核 Checker:

董瓷性

主检 Appraiser:

品情



货物运输条件鉴定书

Certification for Safe Transport of Chemical Goods

号	检验结果及其他事项					
No.	Inspection results and other things					
1	本报告所述锂电池按照《危险品规则》(60版)[以下简称DGR] 3.9.2.6.1(e)规定的质量管理体系进行制造。 本报告所述锂电池不属于因安全原因召回的锂电池。 Lithium cells and batteries listed in this report were manufactured under the quality management programme as described in IATA DGR 60th 3.9.2.6.1(e). Lithium cells and batteries listed in this report are not the defective cells or batteries returned to the manufacturer for safety reasons.					
2	本报告所述锂电池已通过《联合国试验和标准手册》第III部分38.3小节相应测试要求。 Lithium cells and batteries listed in this report are of the types proven to meet the requirements of each applicable test in the UN Manual of Tests and Criteria, Part III, sub-section 38.3.					
3	设备装入由适当材料构造的坚固的刚性外包装内。 The equipment is packed in strong rigid outer packagings constructed of suitable material.					
4	电池具有适当的防短路措施。设备固定在外包装内以免移动,并配备防止发生意外启动的有效手段。 设备固定在外包装内以免移动,并配备防止发生意外启动的有效手段。 Cells and batteries are properly protected to prevent short circuits. The equipment is secured against movement within the outer packaging and is equipped with an effective means of preventing accidental activation.					
5	—当使用航空货运单时,如果托运货物中有贴锂电池标记的包装件,那么必须在"货物名称和数量"栏注明"锂金原电池符合包装说明970第II部分"。 —Where a consignment includes packages bearing the lithium battery mark, the words "lithium metal batteries in compliance with Section II of PI 970" must be shown in the "Nature and Quantity of Goods" box of the air waybill, when an air waybill is used.					
6	每个包装件必须耐久清晰的标识DGR图7.1.C所示标记。包装件必须具有足够的尺寸在其一个面上粘贴未被折叠的标记。本要求不适用于: —包装件仅含有安装在设备(包括线路板)内的银扣电池: 或——托运货物不超过2个包装件,且每个包装件中安装在设备内的电池芯不超过4颗或电池组不超过2颗。——托运货物不超过2个包装件,且每个包装件中安装在设备内的电池芯不超过4颗或电池组不超过2颗。 Each package must be durably and legibly marked with the mark shown in Figure 7.1.C in IATA DGR. The package must be of such a size that there is adequate space to affix the mark on one side of the package without the mark being folded. This requirement does not apply to: —packages containing only button cell batteries installed in equipment (including circuit boards); or —consignments of two packages or less where each package contains no more than four cells or two batteries installed in equipment.					
7						
	-验证码:360466-					

A TOP

Certification for Safe Transport of Chemical Goods



报告结束

