

Product Specifications

FlashCheck Lollipop Waterproof Min/Max Digital Thermometer w/105mm Probe

Measurement Range	-58°F to 392°F (-50°C to 200°C)
Accuracy	±1°F between -4°F to 302°F; otherwise ±1.8°F ±0.5°C between -20°C to 150°C; otherwise ±1°C
Display Resolution	0.1° between -20° to 200° (°C or °F) otherwise 1°
Display Reading Update	1 second
Display Window Size	0.77in W x 0.37in H (19.5mm W x 9.5mm H)
Calibration	N.I.S.T. traceable by lot. Adjustable calibration resistor beneath the screw on back side
Battery	1.5 V size LR44 button alkaline or equivalent
Battery Life	About 5,000 hours in continuous operation
Probe Size	0.14in Dia. x 4.13in L 3.5mm Dia. x 105mm L
Product Size	1.75in W x .77in D x 6.38in L (44.5mm W x 19.5mm D x 162mm L) (Including probe cover)
Body Casing	Polycarbonate and ABS plastic
Certification	CE Mark, Traceable to NIST, RoHS



Model 11036

- °F/°C selectable
- Min/Max memory stores lowest/highest readings until reset
- Can be field calibrated (calibration pot located on back of unit under the screw & o-ring)
- Probe cover with pocket clip on back
- Waterproof housing, IP67 rated

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 11036 20F1

