

Product Specifications

FlashLink USB In-Transit Logger



Measurement Range	-40°F to 122°F (-40°C to 50°C)
Temperature Resolution	0.1°F/°C
Accuracy	±1.0°F from 14°F to 77°F (±0.5°C from -10°C to 25°C); ±2.0°F above 77°F (±1.0°C above 25°C) ±2.0°F below 14°F (±1.0°C below -10°C)
Data Capacity	3823 points
Data Download Time	5 seconds typical for 3823 points
Factory Programmable Alarm Levels	High & Low levels over entire range, displayed on LCD
Battery	Coin Cell Lithium Battery
Dimensions/ Body	1.575" x 3.189" x .575" (40mm x 81mm x 13mm)
Casing	ABS plastic
Weight	1.3 oz. (36 grams)
Shock Resistance	Withstands 3-foot (1 meter) drop to hard surface
Certification	CE Mark, NIST traceable, RoHS Compliant
FAA Compliance	RTCA/DO-160
Display	LCD, Red LED Alarm
IP Rating	IP54 (with silicon cap on)
Storage conditions	-4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation
System Requirements	Windows PC with current operating system, Adobe Reader, FlashPDF software
Download Requirements	Direct USB connection



Models	5-Day	15-Day	45-Day	75-Day
Logging Interval	1 min. 54 Sec	5 min. 40 Sec	16 min. 58 Sec	28 min. 16 Sec
°F Models	20910	20911	20912	20913
°C Models	20914	20915	20916	20917

- Single-use
- Large, easy to read LCD display
- Trip history statistics available on LCD
- USB Connection, no cradle reader or adapter needed
- Patented Shadow Log® feature guarantees data even if the operator fails to start the unit
- Download data with free FlashPDF software

Patent No. 6,088,514

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

SS0078_16D1

