

# GO Nano BLE

GO Nano BLE 蓝牙记录仪

|                   |               |
|-------------------|---------------|
| Model             | TB60D-00      |
| Brand             | Copeland      |
| Temperature range | -40 to 80 ° C |

## Product overview

GO Nano BLE

## Technical specifications

| Parameter           | Value                            |
|---------------------|----------------------------------|
| Model               | TB60D-00                         |
| Brand               | Copeland                         |
| Product family      | GO Nano BLE                      |
| Source category     | Cargo tracking and monitoring    |
| Part number         | Copeland                         |
| Product format      | Series                           |
| Keywords            | GO Nano BLE TB60D-00             |
| Website enabled     | US   CA   MX   AR   CL   PY   UY |
| Can back order      | Yes                              |
| Hazardous good      | No                               |
| Images collected    | 2                                |
| Documents collected | 2                                |

Sales and technical support

|       |                                                        |         |                                                    |       |               |
|-------|--------------------------------------------------------|---------|----------------------------------------------------|-------|---------------|
| Email | <a href="mailto:sales@eofirm.com">sales@eofirm.com</a> | Website | <a href="http://www.eofirm.com">www.eofirm.com</a> | Phone | 0755-84200058 |
|-------|--------------------------------------------------------|---------|----------------------------------------------------|-------|---------------|

Copeland, Cooper-Atkins and related product names and trademarks belong to their respective owners. This document was prepared by EO Temperature Control from publicly available product information. Please refer to the latest manufacturer documentation and the supplied product version for final selection and specifications.