

Product Specifications

FlashLink. NOW 4G/5G Real-Time In-Transit Logger

Temperature Range	-30°C to 70°C (-22°F to 158°F)
Temperature Accuracy	±0.5°C from -10°C to 45°C (±0.9°F from 14°F to 113°F), ±1.0°C (1.8°F) Other
Temperature Resolution	0.1°C/°F
Temperature Sensor Type	Internal Digital Temperature Sensor (NIST traceable)
Temperature Scale	Celsius
Light Sensor Range	0 to 52000 lux
Light Detecton Accuracy	0.01 lux
Usage Type	Single-use
Data Capacity	Max 28800 Readings
Logging Interval	5 Min.
Data Upload Interval	15 Min.
Trip Duration	12-Day (based on logging and uploading intervals)
Cellular	Global LTE Cat-1 for 4G/5G network, with 2G Fallback
SIM	Internal Embedded (Global Data Roaming)
Power Source	Lithium-ion battery, meets UN38.3
Battery Shelf Life	1 year
Logger Dimensions	4.05in x 2.41in x 1.18in (103mm x 61.3mm x 30mm)
Weight	4.6 oz (130 grams)
Waterproof Rating	IP64
Certification	FCC, RoHS, NIST traceable temperature accuracy
PDF Report Backup	Micro USB to USB cable to download full trip PDF report

DeltaTrak manufactures and operates under an ISO 9001:2015
registered quality management system



Model 22390-07

- Next generation of global cellular communications real-time loggers with LCD using 4G/5G LTE/2G
- Precision location accuracy using latest global cellular technology with Wi-Fi triangulation positioning
- Monitors location, temperature, light
- Proactively manage shipment location and conditions to reduce the risk of product loss due temperature excursions
- FlashTrak Cloud Service platform offers different levels of access to optimize user experience and API integration into customer systems. FlashTrak receiver program allows shippers to customize access to alerts and shipment conditions
- USB option to download PDF trip data should network not be available.
- Light sensors alert you to unplanned security access which reduces and averts potential product theft during transportation



SS 22390-07 24G2