

FlashLink. NOW 4G/5G

实时在途记录仪

温度范围 -30° C 至 70° C (-22° F 至 158° F)	
温度精度 (14° F 至 113° F 范围内为 ±0.9° F) , ±1.0° C (2.0° F) 其他	-10° C 至 45° C 范围内为 ±0.5° C
温度分辨率 0.1° C/° F	
温度传感器类型	内部数字温度传感器 (NIST 可追溯)
湿度范围 5% 至 95% RH	
湿度准确度	±3% 从 20% 到 80%RH ±5% 其他
光传感器范围 0 至 52000 lux	
光检测精度 0.01 lux	
震动传感器0-8g 高度 : 5-10cm	
使用类型 一次性使用	
数据容量 最大 28800 个读数	
记录间隔 10 分钟	
数据上传间隔 120 分钟	
行程持续时间	90 天 (基于记录和上传间隔)
蜂窝全球 LTE Cat-1 4G/5G 网络, 具有 2G 回退功能	
内部嵌入式 (全球数据漫游) SIM	
电源 锂离子电池, 符合UN38.3	
电池保质期 1 年	
记录仪尺寸	4.05 英寸 x 2.41 英寸 x 1.18 英寸 (103毫米x61.3毫米x30毫米)
重量 4.9 盎司 (140 克)	
防水等级 IP64	
认证 FCC、RoHS、NIST 可溯源温度精度	
PDF报告备份	Micro USB转USB线下载全程 PDF报告



Model 22393-01

Next generation of global cellular communications real-time loggers with LCD using 4G/5G LTE/2G

Precision location accuracy using latest global cellular technology with Wi-Fi triangulation positioning

Monitors location, temperature, humidity, light, and shock

Proactively manage shipment location and conditions to reduce the risk of product loss due temperature excursions

FlashTrak Cloud Service platform offers different levels of access to optimize user experience and API integration into customer systems. FlashTrak receiver program allows shippers to customize access to alerts and shipment conditions

USB option to download PDF trip data should GSM network not be available.

Light sensors alert you to unplanned security access which reduces and averts potential product theft during transportation

Maritime tracking service options ensure access to different modes of integrated supply chain data.



不锈钢 22393-01 24D1