

# Product Specifications

## FlashLink. Mini PDF In-Transit Logger

|                                    |                                                                                                                                                                                                                                  |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Measurement Range</b>           | -40°F to 140°F (-40°C TO 60°C)                                                                                                                                                                                                   |
| <b>Accuracy</b>                    | ±1.0°F from -4°F to 14°F (±0.5°C from -20°C to -10°C)<br>±0.6°F from 14°F to 50°F (±0.3°C from -10°C to 10°C)<br>±1.0°F from 50°F to 77°F (±0.5°C from 10°C to 25°C)<br>±1.8°F if < -4°F or > 77°F (±1.0°C if < -20°C or > 25°C) |
| <b>Data Download Time</b>          | 5 seconds typical                                                                                                                                                                                                                |
| <b>Factory Programmable Alarms</b> | High & Low levels over entire range                                                                                                                                                                                              |
| <b>Delay Start</b>                 | 30 minutes                                                                                                                                                                                                                       |
| <b>Battery</b>                     | Coin Cell Battery                                                                                                                                                                                                                |
| <b>Dimensions</b>                  | 1.858in x 3.071in x 0.402in<br>(47.2mm x 78mm x 10.2mm)                                                                                                                                                                          |
| <b>Weight</b>                      | 0.854 oz. (24.2 grams)                                                                                                                                                                                                           |
| <b>Shelf Life</b>                  | 18 Months                                                                                                                                                                                                                        |
| <b>Certification</b>               | RTCA/DO-160G Sect 21.5, CE Mark, Calibration traceable to NIST, RoHS Compliant                                                                                                                                                   |
| <b>Display</b>                     | Green and Red LED                                                                                                                                                                                                                |
| <b>Waterproof Rating</b>           | IP54 with silicone cap                                                                                                                                                                                                           |
| <b>Storage Conditions</b>          | -4°F to 122°F (-20°C to 50°C)<br>0% to 95% RH w/o condensation                                                                                                                                                                   |
| <b>System Requirements</b>         | Windows PC with current operating system<br>Adobe Reader                                                                                                                                                                         |
| <b>Download Requirements</b>       | Direct USB connection to PC, tablet or printer                                                                                                                                                                                   |



FlashLink Mini PDF with high visibility locator card

|                                                       |                    |                    |                    |
|-------------------------------------------------------|--------------------|--------------------|--------------------|
| EO: sales@eofirm.com   www.eofirm.com   0755-84200058 |                    |                    |                    |
| <b>Low/High Alarm Settings</b>                        | None               | 2°C/8°C            | 15°C/25°C          |
| <b>Sample Rate</b>                                    | 10 Min             | 5 Min              | 5 Min              |
| <b>Data Capacity</b>                                  | 12,288 data points | 12,288 data points | 12,288 data points |
| <b>Trip Duration</b>                                  | 85 Days            | 42.5 Days          | 42.5 Days          |
| <b>Temperature Scale</b>                              | °F/°C              | °F/°C              | °F/°C              |

- Compact, single-use temperature logger
- Shadow Log® guarantees trip data
- No software required for download
- Built-in USB connector, no special reading device needed
- On-board software automatically creates PDF and CSV reports in °F and °C
- View reports on a PC or tablet
- Recorded data automatically scaled to graph
- GMT/UTC: 0

Patent No. 6,088, 514

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 31010-X 21B1

