

# Product Specifications

## FlashLink. PDF Multi-Use Data Logger

|                                   |                                                                                                                                              |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Measurement Range                 | -40°F to 122°F (-40°C to 50°C)                                                                                                               |
| Temperature Resolution            | 0.2°F /0.1°C                                                                                                                                 |
| Accuracy                          | ±1.0°F from -4°F to 113°F; (±0.5°C from -20°C to 45°C)<br>±2.0°F above 113°F; (±1.0°C above 45°C)<br>±2.0°F below -4°F; (±1.0°C below -20°C) |
| Data Capacity                     | 16,112 points                                                                                                                                |
| Sample Interval                   | 5 minutes                                                                                                                                    |
| Data Download Time                | 30 seconds typical                                                                                                                           |
| Factory Programmable Alarm Limits | High/low limits over entire temp range                                                                                                       |
| Battery                           | Coin Cell Lithium battery                                                                                                                    |
| Dimensions                        | 1.93" x 3.62" x 0.67"<br>(49mm x 92mm x 17mm)                                                                                                |
| Casing                            | ABS plastic                                                                                                                                  |
| Weight                            | 1.6 oz. (45.36 grams)                                                                                                                        |
| Shock Resistance                  | Withstands 3-foot (1 meter) drop to hard surface                                                                                             |
| Certification                     | CE Mark, Calibration traceable to NIST, ROHS Compliant, BSS 7061 Compliant                                                                   |
| Display                           | LCD, Red LED Alarm                                                                                                                           |
| Storage Conditions                | -4°F to 122°F (-20°C to 50°C) 0% to 95% RH w/o condensation                                                                                  |
| PDF Standards                     | Complies with ISO19005-1, PDF/A, 21 CFR Part 11                                                                                              |
| System Requirements               | Windows PC with current operating system<br>Adobe Reader                                                                                     |
| Download Requirements             | Direct USB connection                                                                                                                        |



### Models

|    |       |
|----|-------|
| °F | 40202 |
| °C | 40203 |

- One unit can be used multiple times
- No software or PC needed to program logger
- No software needed to download data
- Built-in USB connector, no special reading devices required
- Stops recording after downloading data
- Automatically creates secure PDF report and CSV file
- Push-button resets and restarts unit for next use
- Temperature statistics available on LCD
- Service available to custom configure logging parameters, alarms, delayed start

DeltaTrak manufactures products under an ISO 9001:2015 registered quality management system

SS 40202-X\_18J1

