


# Product Specifications

## FlashCheck. Lollipop Auto Cal Min/Max Antimicrobial Thermometer

|                               |                                                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Measurement Range</b>      | -40°F to 311°F (-40°C to 155°C)                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Operating Range</b>        | 32°F to 122°F (0°C to 50°C)                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Accuracy</b>               | $\pm 0.9^{\circ}\text{F}$ from -40°F to +14°F<br>$(\pm 0.5^{\circ}\text{C}$ from -40°C to -10°C)<br>$\pm 0.5^{\circ}\text{F}$ from +14°F to +68°F<br>$(\pm 0.3^{\circ}\text{C}$ from -10°C to +20°C)<br>$\pm 0.9^{\circ}\text{F}$ from +69°F to +239°F $(\pm 0.5^{\circ}\text{C}$ from +21°C to +115°C)<br>$\pm 1.8^{\circ}\text{F}$ from 240°F to +311°F $(\pm 1.0^{\circ}\text{C}$ from 116°C to 155°C) |
| <b>Sensor</b>                 | Thermistor                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Display Resolution</b>     | 0.1°F/°C                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Display Reading Update</b> | 1 second                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Display Window Size</b>    | 1.3in W x 0.9in H<br>(32.9mm W x 22.9mm H)                                                                                                                                                                                                                                                                                                                                                                |
| <b>Calibration</b>            | Automatic calibration feature                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Battery</b>                | Button cell alkaline                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Body Casing</b>            | ABS plastic with antimicrobial additive                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Probe Length</b>           | 4.13in (105mm)                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Probe Diameter</b>         | 0.14in (3.56mm),<br>reduced tip 0.1in (2.5mm)                                                                                                                                                                                                                                                                                                                                                             |
| <b>Weight</b>                 | 1.3oz (37.6g)                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Waterproof Rating</b>      | IP65                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Factory Calibration</b>    | NIST traceable calibration certified                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Compliance Certificate</b> | Manufacturers certificate of compliance available from DeltaTrak, NIST Traceable, NSF, CE                                                                                                                                                                                                                                                                                                                 |



### Model 11050

- Antimicrobial additive inhibits growth of bacteria, mould and fungus
- Min/Max memory stores lowest/highest readings
- Automatic calibration feature
- IP65 Waterproof housing
- Sealed unibody construction
- Small-diameter probe ideal for measuring temperature of "thin mass" food such as meat patties and chicken/fish fillets (FDA Food Code 4-302.12 (B))
- NSF certified
- °F/°C selectable

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system



SS 11050 21L2

